

URANIUM CORPORATION OF INDIA LTD. JADUGUDA
(A GOVT. OF INDIA, DEPARTMENT OF ATOMIC ENERGY ENTERPRISE)

DATE 30-4-03

SCALE NTS

REV. 0

SUB. SQ. TAPER HEAD BOLTS FOR PRY. SEC.


DRAWN [Signature]

CHECKED [Signature]

AND PYROLUSITE MILL, CONE CRUSHER.

APPROVED [Signature]

DRG. NO. UCI/M-891/A



ITEM NO.	SIZE	A ϕ	B	C	D sq.	E sq.	F	REF. DRG. NO. UCI/M-93/A.
1	7/8" x 13"	7/8"	13"	1 1/4"	1 1/2"	1 1/32"	3 1/4"	FOR GRID LINER, PRY. SEC. MILL & CONE CRUSHER
2.	1 1/8" x 4 1/2"	1 1/8"	4 1/2"	1 1/2"	2"	1 1/4"	3"	FOR FEED END LINER & SHELL LINER (PRY. SEC. MILL)
3.	3/4" x 4 1/2"	3/4"	4 1/2"	1"	1 3/8"	1 1/32"	2 3/4"	FOR DISCHARGED END LINER, P & S. MILL
4.	3/4" x 3"	3/4"	3"	1 1/4"	1 1/2"	1"	2"	FOR PYROLUSITE MILL

MAT'L- En-8, FORGED & HEAT TREATED STEEL.

TENSILE STRENGTH 40/45 TON/SQ. INCH.

HARDNESS 200-230 B.H.N.