

## Technical Specification:

I.I. NVR 8 Channel 700:026:097:002 (Material Code)

## Specification for NVR

<b>Video/Audio Input</b>	
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1kΩ)
IP video input	8-ch
<b>Network</b>	
Remote connection	128
Incoming bandwidth	80Mbps
Outgoing bandwidth	80Mbps
<b>Video/Audio Output</b>	
HDMI/VGA output	1-ch, resolution: 1920 × 1080P /60Hz, 1600 × 1200/60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz
Recording Resolution	6MP/5MP/4MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Frame Rate	Main stream: 50 fps (P) / 60 fps (N) Sub-stream: 50 fps (P) / 60 fps (N)
Audio Output	1-ch, RCA (Linear, 1kΩ) Synchronous Playback: 8-ch
<b>Decoding</b>	
Capability	5-ch@1080P
Live view / Playback	6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
<b>Hard Disk</b>	
SATA	2 SATA interfaces for 2 HDDs
Capacity	Up to 6TB capacity for each HDD
<b>External Interface</b>	
Network Interface	1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
USB Interface	1 × USB 2.0 and 1 × USB 3.0
Alarm In	4-ch(optional)
Alarm Out	1-ch(optional)
<b>POE</b>	
Supported Standard	AF and AT
Interface	8 Independents 100 Mbps PoE networks
<b>General</b>	
Power Supply	100-240VAC
Working Temperature	10 to 50 Degree Centigrade
Working Humidity	10 % ~ 90 %
<b>Make</b>	Alcon, Honeywell, Hikvision, Samsung, Bosch, ACTI, CP Plus

*Sulab Kumar*  
01/10/2019