

**Compliance Status of Environmental Condition with respect to Mohuldih Mine of Uranium Corporation of India Limited as on September 2024**

<b>Sl. No.</b>	<b>Specific conditions</b>	<b>Status of Compliance</b>
i.	<i>The environmental clearance is subject to approval of the State Landuse Department, Government of Jharkhand for diversion of agricultural land for non-agricultural use.</i>	The competent authority has delivered the possession of 22.10 acre raity land (agriculture land) dated 25.01.2008 in favor of Uranium Corporation of India Limited for setting of Mohuldih mine. In principle, agriculture land has been acquired for non-agricultural purpose through competent authority. Certificate of possession has been submitted to the ministry.
ii.	<i>The environmental clearance is subject to grant of forestry clearance for diversion of 44.60 ha forestland. Necessary forestry clearance under the Forest (Conservation) Act, 1980 for an area of 44.60 ha forestland shall be obtained before starting mining operation in that area.</i>	The Ministry of Environment and Forest has granted forestry clearance of 44.60 ha forestland under the Forest (Conservation) Act, 1980 vide letter no. 8-58/2007-FC dated 01 <sup>st</sup> July 2010.
iii.	<i>All the conditions stipulated by the SPCB in their NOC shall be effectively implemented.</i>	NOC has been obtained from Jharkhand State Pollution Control Board (JSPCB) vide letter no. JA/2655/W/N-147 dated 04.08.2006. Condition stipulated their under is being complied.
iv.	<i>Top soil, if any, should be stacked with proper slope at earmarked site(s) only with adequate measures and should be used for reclamation and rehabilitation of mined out areas.</i>	As Mohuldih Mine is an underground mine, availability of top soil is negligible. Small quantity of top soil available during construction of decline was used within mine premises.
v.	<i>The over burden shall be stacked at earmarked dump site(s) only and should not be kept active for long period. Proper terracing of OB dump should be carried out so that the overall slope shall not exceed 28 degree. The OB dumps should be scientifically vegetated with suitable native species to prevent erosion and surface run off. Monitoring and management of rehabilitated areas should continue until the vegetation becomes self-sustaining. Compliance status should be submitted to the Ministry of Environment &amp; Forests and its Regional Office, Bhubaneswar on six monthly basis.</i>	As the project is an underground mine, the overburden is not available. The waste rock generated during development period of mine is stacked at earmarked location within mine premises. The waste rock generated during mining activity is used to fill the mine voids in underground workings. Progressive reclamation of waste dump shall be done.
vi.	<i>Catch drains and siltation ponds of appropriate size</i>	OB dump and mine pit are not applicable in the

Sl. No.	Specific conditions	Status of Compliance
	<p><i>should be constructed for the working pit and OB dump to arrest flow of silt and sediment. The water so collected should be utilized for watering the mine area, roads, greenbelt development etc. The drains should be regularly desilted, particularly after monsoon, and maintained properly.</i></p> <p><i>Garland drain (size, gradient and length) shall be constructed for both mine pit and OB dump and sump capacity should be designed keeping 50 % safety margin over and above peak sudden rainfall (based on 50 years data) and maximum discharge in the area adjoining the mine site. Sump capacity should also provide adequate retention period to allow proper settling of silt material. Sedimentation pits should be constructed at the corners of the garland drains and desilted at regular intervals.</i></p>	<p>present context due to underground mining project. However, small waste dump at surface has been earmarked within mine premises. 381 m garland drain has been constructed to arrest the silt and sediment from the waste dump area during rainy season which ultimately merge to desilting pond. Mine de-watering water is collected in de-silting cum mine water pond. The water so collected is utilized for watering the mine area, roads, greenbelt development etc. Photograph of mine de-silting pond is attached.</p>
vii.	<p><i>Dimension of the retaining wall at the toe of the dump and OB benches within the mine to check run-off and siltation should be based on the rain fall data.</i></p>	<p>Not applicable as explained above.</p>
viii.	<p><i>Regular monitoring of subsidence movement on the surface over working area and impact on water bodies/ vegetation/ structures/ surrounding should be continued till movement ceases completely. In case of observation of any high rate of subsidence movement, appropriate measures should be taken to avoid loss of life and material. Cracks should be effectively plugged with ballast and clayey soil /suitable material.</i></p>	<p>Cut and fill method of mining is practiced for Mohuldih mining project, subsidence is not envisaged. The voids created during mining activities are filled up with waste rock and sand. The same practice has been adopted for nearby underground mines of UCIL.</p>
ix.	<p><i>The project authorities should check the possibility of existence of fault(s) before deciding about the thickness of safe barrier required to be maintained between the working face and the river in consultation with the Director General Mines &amp; Safety (DGMS). De-pillaring should also be carried out after taking prior approval of the DGMS</i></p>	<p>No river exists within core zone of the project.</p>
x.	<p><i>Study report on subsidence and stage wise development plan starting from 5th year of</i></p>	<p>As explained in sr. no. (viii), subsidence is not envisaged. The approved mine plan from the</p>

Sl. No.	Specific conditions	Status of Compliance
	<i>operation till the end of the mine at an interval of 5 years should be submitted to the Ministry and its Regional Office, Bhubneshwar within six months.</i>	competent authority, Atomic Minerals Directorate for Exploration & Research, Govt. of India has been submitted to the ministry. Mine plan after at the interval of 5 <sup>th</sup> year of operation till the end of mine will be submitted.
xi.	<i>All the mine entries should be above the highest flood level to avoid any anticipated flooding of mine from surface water during rainy season.</i>	All mine entries has been kept above the highest flood level (140 mRL).
xii.	<i>In areas where subsidence is anticipated in shallow uranium ore occurrence, such areas be identified and provided with garland drains to ensure draining of water and avoid ingress of the same in to the underground mine.</i>	Subsidence is not envisaged as explained in sr. no. (viii). Necessary action has been taken to avoid ingress of water into the underground mine. Garland drain has been constructed to divert the rain water around the mine entry.
xiii.	<i>Suitable embankment of proper dimensions should be constructed to protect the area from flood water during rainy season.</i>	The profile of the area is hilly therefore flooding of mining area is not envisaged. Proper drainage arrangement has been made to divert rainwater of the catchments area. Embankment may not be required for such purpose. Construction of storm water drain around the installation has been completed.
xiv.	<i>Green belt should be raised in an area of 24.01 ha by planting the native species around the ML area, OB dump sites, roads etc. in consultation with the local DFO/Agriculture Department. The density of the trees should be around 2500 plants per ha.</i>	Progressive greenbelt development/ plantation have been started in vacant areas, around installation, along the roads and along the boundary. Total 26060 numbers of native trees plantations have been completed up to September 2024 which covers about 22.67 ha area. Photographs showing greenbelt development and plantation are attached.
xv.	<i>The project authority should implement suitable conservation measures to augment ground water resources in the area in consultation with the Regional Director, Central Ground Water Board.</i>	Rainwater harvesting scheme has been implemented in Mohuldih mines for augmentation of ground water resource. Rainwater harvesting recharge pond of size 26 m x 15 m X 2.5 m has been constructed within Mohuldih mine premises. The pond consists of two number of ground water recharge well of depth 20 m inserted with perforated PVC pipe having 6" dia. Filter bed chambers of size 250 mm sand top layer 250 mm gravels and 250 mm and pebbles has been layered inside the recharge well for filtration. Geo tagged

Sl. No.	Specific conditions	Status of Compliance
		<p>photograph of RWH recharge pond is attached.</p> <p>In addition to above, desilting cum rainwater harvesting pond of volumetric capacity 16300 m<sup>3</sup> has been constructed in northern side of the mining lease. Mine discharge water is collected in the pond. The de-silted mine water is used in the premises and excess is sent to ore processing plant Turamdih for use.</p> <p>Photograph of desilting cum rain water pond is attached.</p>
xvi.	<p><i>Regular monitoring of ground water level and quality should be carried out by establishing a network of existing wells and constructing new piezometers during the mining operation. The monitoring should be carried out four times in a year - pre-monsoon (April-May), monsoon (August), post-monsoon (November) and winter (January) and the data thus collected may be sent regularly to Ministry of Environment and Forests , its Regional Office, Bhubaneswar, Central Ground Water Authority and Regional Director, Central Ground Water Board.</i></p>	<p>Monitoring of ground water level is carried out around the project by network of existing wells. Water levels during April &amp; August 2024 varies as 5.40 to 8.75 m and 5.10 to 11.10 m from existing ground level respectively. The ground water quality is monitored four times in a year for pre-monsoon, monsoon, post-monsoon and winter. The ground water quality meet the drinking water quality as per IS:10500:2012. Uranium and Radium values in 11 samples during April 2024 varies from 0.3 - 6.1 µg/l and 5.0 - 28 mBq/l respectively which are well within drinking water standards (U- 60 µg/l and <sup>226</sup>Ra- 300 mBq/l).</p> <p>Ground Water quality analyzed by M/s Aditi R&amp;D Services, Dhanbad is attached.</p> <p>Monitoring of ground water level and quality is regularly sent to the Regional Director, Central Ground Water Board, Patna (ref: UCIL/ENV/MHD/CGWB/05/2024 dated 03.05.2024).</p>
xvii.	<p><i>The project authorities should obtain prior approval of the competent authority for drawal of groundwater required for the project.</i></p>	<p>No groundwater withdrawal has been planned for industrial purpose except drinking and pit head bath. Mine discharge water is used for industrial purpose. NOC from CGWA has been granted vide letter no CGWA/NOC/MIN/ORIG/2022/14351 dated 18.01.2022 which is valid up to 17.01.2024 for dewatering during mining activity. Renewal application has been made on 13.01.2024.</p>
xviii.	<p><i>The project authorities should undertake sample survey to generate data on pre-project community health status within a radius of 1km from proposed mine.</i></p>	<p>Pre-project community health survey report has been submitted to the ministry vide letter no. UCIL/ENV/MHLD/MoEF/12/10 dated 26.11.2010. Latest Health Survey Report has been submitted.</p>

Sl. No.	Specific conditions	Status of Compliance
xix.	<i>The mineral handling plant should be provided with adequate number of high efficiency dust extraction system. Loading and unloading areas including all the transfer points should also have efficient dust control arrangements. These should be properly maintained and operated.</i>	Not applicable. No mineral handling plant is envisaged. Ore from Mohuldih Mine is processed at nearby UCIL's Ore Processing Plant at Turamdih.
xx.	<i>Consent to operate should be obtained from SPCB before starting mining activities.</i>	JSPCB has granted Consent to Operate vide letter no. JSPCB/RO/JSR/CTO-9047962/2021/124 dated 12.10.2021 which is valid up to 31.03.2026.
xxi.	<i>Vehicular emissions should be kept under control and regularly monitored. Measures shall be taken for maintenance of vehicles used in mining operations and in transportation of mineral. Overloading of trucks should be avoided to stop spillage. The loaded trucks be covered with tarpaulin sheets to prevent spillage of ore.</i>	Adequate measure is taken for vehicle maintenance to control emissions during transportation. Cover truck is used and overloading is avoided to prevent the spillages during transportation.
xxii.	<i>The project proponent should take all precautionary measures during mining operation for conservation and protection of endangered fauna such as elephant etc. spotted in the study area in consultation with the concerned forest officials. Action plan for conservation of flora and fauna shall be prepared and implemented in consultation with the State Forest and Wildlife Department. Necessary allocation of funds for implementation of the conservation plan shall be made and the funds so allocated shall be included in the project cost. Copy of action plan may be submitted to the Ministry and its Regional Office, within 3 months.</i>	No endangered fauna has been spotted in area. UCIL has submitted the action plan for conservation of fauna, if any to MoEFCC vide our letter no. UCIL/NWP/ENV/MoEF/5/08 dated 12.05.2006. Report of DFO, Seraikela Forest Division regarding occurrence of schedule-I fauna within 10 km radius of the project has been submitted to the ministry.
xxiii.	<i>Monitoring of background radiation levels in water, soil and ambient air should be carried out periodically in the study area (core and buffer zone) of the project.</i>	Monitoring of background radiation levels in water, ambient air (Gamma Radiation Survey) & soil is carried out by Health Physics Unit of BARC in core & buffer zone of the project. Water analysis report has been furnished in condition no. XVI. The environmental Gamma radiation survey conducted during April to September 2024 in core & buffer zone shows the variation as 0.08 to 2.17 $\mu\text{Gy/hr}$ & 0.08 to 0.17 $\mu\text{Gy/hr}$ respectively.

Sl. No.	Specific conditions	Status of Compliance										
xxiv.	<p><i>The plants growing in the area, soil invertebrate animals and local agricultural produce should be analysed to check the build up of radioactivity levels, if any.</i></p>	<p>Analysis of invertebrate animals (snail) from four locations within mining lease has been analyzed by Health Physics Unit, BARC to check the buildup of radioactivity levels. Results is as under:</p> <table border="1" data-bbox="889 415 1468 510"> <thead> <tr> <th>Date of Sampling</th> <th>U (Nat) (mg/kg)</th> <th><sup>226</sup>Ra (Bq/kg)</th> <th>Th (Bq/kg)</th> <th><sup>210</sup>Po (Bq/kg)</th> </tr> </thead> <tbody> <tr> <td>06.08.2024</td> <td>&lt;0.1</td> <td>1.6</td> <td>0.53</td> <td>5.06</td> </tr> </tbody> </table>	Date of Sampling	U (Nat) (mg/kg)	<sup>226</sup> Ra (Bq/kg)	Th (Bq/kg)	<sup>210</sup> Po (Bq/kg)	06.08.2024	<0.1	1.6	0.53	5.06
Date of Sampling	U (Nat) (mg/kg)	<sup>226</sup> Ra (Bq/kg)	Th (Bq/kg)	<sup>210</sup> Po (Bq/kg)								
06.08.2024	<0.1	1.6	0.53	5.06								
xxv.	<p><i>Discharges from the treatment plant and settling pits should be constantly monitored for concentration of radio nuclides.</i></p>	<p>Treatment Plant at Mohuldih Mine is not envisaged. Mine discharge water is collected in de-silting pond. After silt removal, water is reused for industrial purpose. The excess mine discharge is transferred to the nearby UCIL's Turamdih Ore Processing Plant for reuse. Construction of de-silting ponds, pumping station and laying of pipeline has been completed. There is no discharge from Mohuldih Mine. Mine Water has also been analyzed by M/s Aditi R&amp;D Sevices, Dhanbad.</p>										
xxvi.	<p><i>Sludge from the treatment plant and settling pit should be transported in safe containment.</i></p>	<p>Sludge form de-silting tank is transported to tailing pond of nearby Turamdih ore processing plant of UCIL. Sludge of treatment plant is not envisaged as Mohuldih project does not have treatment facility within premises.</p>										
xxvii.	<p><i>Land oustees and land losers should be compensated as per the State Government norms.</i></p>	<p>A compensation amount of Rs. 88,734,45/- has been paid to land looser against 24.15 acre of land for mine facility and road.</p>										
xxviii	<p><i>Wet drilling and water spraying on muck should be practiced to reduce generation of silica and low level of radioactivity in the work place. The external radiation dose should be monitored quarterly to ensure that workers engaged in the work place are not over exposed.</i></p>	<p>Wet drilling is practiced during mine development activities. Dust, alpha activity and external radiation dose rate is being monitored in the work place by BARC. The respirable siliceous dust at 14 locations &amp; alpha activity values at 14 locations of the work place during April to August 2024 varies from 0.10 to 0.74 mg/m<sup>3</sup> (permissible value 0.80 mg/m<sup>3</sup>) &amp; 9 to 43 mBq/m<sup>3</sup> (permissible limit 150 mBq/m<sup>3</sup>) respectively. The external gamma dose rate at 50 locations in workplace varies from 0.08 to 2.17 µGy/h (Permissible limit: 8 µGy/h).</p>										
xxix.	<p><i>A Final Mine Closure Plan along with details of Corpus Fund should be submitted to the Ministry of Environment &amp; Forests 5 years in advance of final mine closure for approval.</i></p>	<p>A final mine closer plan will be submitted to MoEFCC before 5 years of mine closer.</p>										

Sl. No.	General conditions	Status of Compliance
i.	<i>No change in mining technology and scope of working should be made without prior approval of the Ministry of Environment and Forests.</i>	No change in mining technology & scope of working shall be made without prior approval of the Ministry of Environment & Forest.
ii.	<i>No change in the calendar plan including excavation, quantum of mineral uranium and waste should be made.</i>	No change in the calendar plan including excavation and quantum of mineral shall be made.
iii.	<i>At least four ambient air quality monitoring stations should be established in the core zone as well as in the buffer zone for RPM, SPM, SO<sub>2</sub>, NO<sub>x</sub>, and CO monitoring. Location of the stations should be decided based on the meteorological data, topographical features and environmentally and ecologically sensitive targets in consultation with the State Pollution Control Board. Data on ambient air quality (RPM, SPM, SO<sub>2</sub>, NO<sub>x</sub>, and CO) should be regularly submitted to the Ministry including its Regional Office at Bhubaneswar and to the State Pollution Control Board/Central Pollution Control Board once in six months.</i>	Four ambient air quality monitoring station has been established in core & buffer zone based on the metrological data, topographical features and environmentally ecological sensitive targets. Ambient air quality monitored during October 2023 to March 2024 at four locations in core and buffer zones in terms of PM <sub>10</sub> , PM <sub>2.5</sub> , SO <sub>2</sub> , NO <sub>x</sub> , CO, Pb and Ni parameters are found within the permissible standards. Ambient Air Quality & Noise Level has also been monitored by M/s Envirocheck, Dhanbad.
iv.	<i>Adequate measures should be taken for control of noise levels within prescribed standards. Workers engaged in blasting and drilling operations, operations of HEMM, etc., should be provided with ear plugs /muffs.</i>	Total 4165 nos. of Personnel protective equipment has been provided to workers engaged in blasting & drilling operations during April to September 2024. Noise level is monitored periodically which vary from 52 to 72 dB(A) in the month of June & July 2024. Values are within permissible limits [75 dB(A)].
v.	<i>Industrial wastewater (workshop and waste water from the mine) should be properly collected, treated so as to conform to the standards prescribed under GSR 422(E) dated 19th May 1993 and 31st December 1993 or as amended from time to time. Oil and grease trap should be installed before discharge of effluents from workshop.</i>	Mine water discharge during mining operation is collected in de-silting tank. De-silted water is used for industrial purpose within premises and excess water, if any, is being pumped to Turamdih ore processing plant for treatment and reuse. Oil and grease trap has been constructed at vehicle maintenance area. Value of oil & grease in mine water is 1.6 mg/l.
vi.	<i>Personnel working in dusty areas should wear protective respiratory devices and they should also be provided with adequate training and information on safety and health aspects. Occupational health surveillance programme of the workers should be undertaken periodically to observe any contractions due to exposure to radioactive mineral dust and take corrective measures, if needed. The same programme may be extended to adjoining villages also.</i>	PPE is provided to workers. Vocational Training Officer conducts various training programs e.g. initial, refresher, special & development trainings on occupational health & safety and other topics as per the certified schedule of DGMS. Pre employment medical checkup is done. Workers engaged in mine are being monitored for occupational health periodically, as per AERB guideline. During April to September 2024, total 64 employees were medically examined & 73 employees were given vocational training from mine.

Sl. No.	General conditions	Status of Compliance																					
vii.	<i>A separate environmental management cell with suitable qualified personnel should be set up under the control of a senior Executive, who will report directly to the Head of the organization</i>	Environmental Engineering Cell (EEC) has been set up at Turamdih with suitable qualified personnel. EEC is under direct supervision of DGM (Civil & Environment) who report to the Director of the organization. All the environmental management activities related to this project is carried out by EEC. At mines level, safety meeting is held on monthly basis and members from Health Physics Division, BARC and EEC is present to monitor and address the radiological environmental safety.																					
viii.	<i>The funds earmarked for environmental protection measures should be kept in separate account and should not be diverted for other purposes. Year-wise expenditure should be reported to the Regional Office, Bhubaneswar of the MoEF and to the ministry.</i>	Fund for environmental protection measure is made available as under: <table border="1" data-bbox="898 730 1458 1255"> <thead> <tr> <th data-bbox="898 730 954 783">S N</th> <th data-bbox="954 730 1336 783">Activity</th> <th data-bbox="1336 730 1458 783">Cost (in lakhs)</th> </tr> </thead> <tbody> <tr> <td data-bbox="898 783 954 930">1</td> <td data-bbox="954 783 1336 930">Expenditure incurred for construction of desilting pond, pipeline from Mohuldih Mine to Ore Processing Plant Turamdih and tree plantation.</td> <td data-bbox="1336 783 1458 930">146.04</td> </tr> <tr> <td data-bbox="898 930 954 982">2</td> <td data-bbox="954 930 1336 982">Operations and Maintenance Cost of MWTP (2023-24)</td> <td data-bbox="1336 930 1458 982">24.46</td> </tr> <tr> <td data-bbox="898 982 954 1045">3</td> <td data-bbox="954 982 1336 1045">Construction of Rain water Harvesting Pond.</td> <td data-bbox="1336 982 1458 1045">3.88</td> </tr> <tr> <td data-bbox="898 1045 954 1129">4</td> <td data-bbox="954 1045 1336 1129">Water pumping cost from mine to Turamdih Ore Processing Plant in the year 2023-24.</td> <td data-bbox="1336 1045 1458 1129">8.95</td> </tr> <tr> <td data-bbox="898 1129 954 1192">6</td> <td data-bbox="954 1129 1336 1192">Cost of water sprinkling in the year 2023-24.</td> <td data-bbox="1336 1129 1458 1192">1.55</td> </tr> <tr> <td data-bbox="898 1192 954 1255">7</td> <td data-bbox="954 1192 1336 1255">Cost of environmental monitoring for the year 2023-24.</td> <td data-bbox="1336 1192 1458 1255">12.30</td> </tr> </tbody> </table>	S N	Activity	Cost (in lakhs)	1	Expenditure incurred for construction of desilting pond, pipeline from Mohuldih Mine to Ore Processing Plant Turamdih and tree plantation.	146.04	2	Operations and Maintenance Cost of MWTP (2023-24)	24.46	3	Construction of Rain water Harvesting Pond.	3.88	4	Water pumping cost from mine to Turamdih Ore Processing Plant in the year 2023-24.	8.95	6	Cost of water sprinkling in the year 2023-24.	1.55	7	Cost of environmental monitoring for the year 2023-24.	12.30
S N	Activity	Cost (in lakhs)																					
1	Expenditure incurred for construction of desilting pond, pipeline from Mohuldih Mine to Ore Processing Plant Turamdih and tree plantation.	146.04																					
2	Operations and Maintenance Cost of MWTP (2023-24)	24.46																					
3	Construction of Rain water Harvesting Pond.	3.88																					
4	Water pumping cost from mine to Turamdih Ore Processing Plant in the year 2023-24.	8.95																					
6	Cost of water sprinkling in the year 2023-24.	1.55																					
7	Cost of environmental monitoring for the year 2023-24.	12.30																					
ix.	<i>The Regional Office of this Ministry located at Bhubaneswar shall monitor compliance of the stipulated conditions. The project authorities should extend full cooperation to the officer (s) of the Regional Office by furnishing the requisite data / information / monitoring reports.</i>	Uranium Corporation of India Ltd. is committed to take action of any requirement/suggestion of the Ministry for safeguard of environment. We are extending our full co-operation to officials of Regional Office of MoEFCC, Ranchi.																					
x.	<i>The project proponent shall submit six monthly report on the status of the implementation of the stipulated environmental safeguards to the Ministry of Environment and Forests, its Regional Office, Bhubaneshwar, Central Pollution Control Board and State Pollution Control Board.</i>	Six monthly compliance report is being sent to MoEF & JSPCB on regular basis.																					
xi.	<i>A copy of the clearance letter will be marked to concerned Panchayat / local NGO, if any, from whom suggestions / representation has been received while</i>	Not applicable.																					

Sl. No.	General conditions	Status of Compliance
	<i>processing the proposal.</i>	
xii.	<i>The project authorities should inform to the Regional Office located at Bhubaneshwar regarding date of financial closures and final approval of the project by the concerned authorities and the date of start of land development work.</i>	Project has been approved by the competent authority. Land development has been started on 29.05.2007.
xiii.	<i>State Pollution Control Board should display a copy of the clearance letter at the Regional office, District Industry Centre and Collector's / Tehsildar's Office for 30 days.</i>	Complied with State Pollution Control Board, Ranchi.
xiv.	<i>The project authorities should advertise at least in two local newspapers widely circulated, one of which shall be in the vernacular language of the locality concerned, within 7 days of the issue of the clearance letter informing that the project has been accorded environmental clearance and a copy of the clearance letter is available with the State Pollution Control Board and also at web site of the Ministry of Environment and Forests at <a href="http://envfor.nic.in">http://envfor.nic.in</a> and a copy of the same should be forwarded to the Regional Office of this Ministry located Bhubaneshwar.</i>	UCIL had advertised in local newspaper namely Uditvani & Dainik Jagran on 06.04.2008 which is widely circulated in the region.

*Rain water harvesting pond within premises of Mohuldih Mines*



*Desilting –cum- Rainwater Harvesting Pond*



Plantation at Mohuldih Mines

