

| Sl. no. | Description of Items   | Qty.    | Unit Price (In INR) | Total Price RS |
|---------|--|---------|---------------------|----------------|
| 1a.     | <p><b>Bore hole stress meter:</b><br/> Supply of SME model 2270 vib. wire type bore hole stress meter to monitor the stresses/ load developed inside the pillar. It is suitable for 10 meter deep installation and 11 m cable length having the following specifications.</p> <p>a) Type : Vibrating wire<br/> b) Capacity : 0 - 500 KSC or specify.<br/> c) Bore hole dia. : Suitable for 40 to 42 mm.<br/> d) Installation depth : 10 m.<br/> e) Accuracy : <math>\pm 1\%</math> fsd<br/> f) Overload : 150% of fsd<br/> Other detail specifications are as per literature attached.</p> | specify |                     |                |
| 1b.     | Supply of Stress meter installation tool suitable for 10 meters deep installation.   | 1 set   |                     |                |
| 2.      | <p><b>MPBX - 3 POINT:</b><br/> Supply of SME model 2450 vibrating wire type three point bore hole extensometer with groutable type anchors, reference head, steel rod, PVC pipe, Grout and vent pipe, vibrating wire displacement sensors and all other required mounting accessories to monitor the bed/ roof separation at different height having the following specification.</p> <p>Type : Vib. wire type<br/> Anchor depth : 5, 10 &amp; 15 m.<br/> Measuring range : 50 to 200 mm.</p>  | specify |                     |                |