

4000 count digital millimeter with following feature and technical specification

- Temperature (°C) measurement
- Relative mode
- Basic dc accuracy
- Automatic and manual range
- Display hold function
- Diode and continuity test with buzzer
- Cover designed for easy hanging
- Category safety rating: IEC 1010-1: CAT I 1000 V, CAT II 600 V, CAT III 300 V
- Automatic shutdown
- Easily replaceable battery design
- **One-year warranty**
- 500 hours battery life
- Voltage AC, Voltage DC, resistance, capacitance, continuity beeper, diode test, A ac, A dc all in a durable holster
- Rugged and durable design – all inputs, ranges and functions are protected up to 1000 V

Technical Specifications		
V ac	Range	0.1 mV to 1000 V
	Accuracy	$\pm (1.0 \% + 3 \text{ counts})$
	AC Response	40 Hz to 500 Hz
V dc	Range	0.1 mV to 1000 V
	Accuracy	$\pm (0.5 \% + 3 \text{ counts})$
	AC Response	0.1 $\Omega$ to 40 M $\Omega$
Ohms	Range	0.1 $\Omega$ to 40 M $\Omega$
	Accuracy	$\pm (0.4 \% + 2 \text{ counts})$
A ac	Range	0.1 mA to 10 A
	Accuracy	$\pm (1.5 \% + 3 \text{ counts})$
	AC Response	40 Hz to 200 Hz
A dc	Range	0.1 mA to 10 A
	Accuracy	$\pm (1.0 \% + 3 \text{ counts})$
Capacitance	Range	0.01 nF to 100 $\mu$ F
	Accuracy	$\pm (2.0 \% + 5 \text{ counts})$
Hz and Duty Cycle	Range	10 Hz to 100 kHz
	Accuracy	$\pm (0.1 \% + 3 \text{ counts})$
Temperature measurement	Range	-55 °C to 400 °C
	Accuracy	$\pm (2.0 \% + 1 \text{ }^{\circ}\text{C})$
Standard Accessories	1. Fitted Battery 2. Standard Test Lead	
Optional Accessories	1. Meter Hanging Kit (TPAK) 2. Twist Guard Test Lead (TL 175)	
Make & Model	Model : 17B, Make: Fluke	

/ *Handwritten signature*